

DIVOT PATCH

Non Shrink Concrete Repair Mortar

DIVOT PATCH

VERSATILE DIVOT PATCH is a specially formulated blend of fast-setting, shrinkage compensated cements and polymer, designed to fill and smooth virtually all masonry surfaces. VERSATILE DIVOT PATCH is easy to apply, hardens quickly without shrinking, and produces a smooth surface that is suitable for painting, sealing, and coating in as little as 15 minutes. Through its rapid curing mechanism, DIVOT PATCH eliminates the curing time associated with ordinary cement and latex patch systems. Less downtime saves money while still allowing for last minute repairs before subsequent coating applications.

Use DIVOT PATCH to fill in surface defects such as spalls, gouges, cracks, dents, chips, scrapes, and honeycombs. DIVOT PATCH contains no course filler or sand, allowing it to be applied at true feather-edge thickness by steel trowel or putty knife to any prepared surface.

Features and Advantages:

- ✓ No priming required
- ✓ Just add water mix reduces on-site errors
- ✓ Rapid hardening
- ✓ No curing required
- ✓ Adheres to most substrates
- ✓ Shrinkage compensated
- ✓ Easy workability
- ✓ Natural cement gray color
- ✓ Compatible with most sealers and cementitious toppings

Suitable for Use over:

- ✓ Concrete floors
- ✓ Concrete walls
- ✓ Pre-cast concrete
- ✓ Plywood
- ✓ Painted surfaces*
- ✓ Tile*

*Limitations apply

Note: Divot Patch should not be used over gypsum based products.



Spalled Concrete



Spalled Concrete
filled with DIVOT
PATCH



1-800-535-3325
Tel: 310-632-6500
Fax: 310-632-6515
sales@deckcoatings.com
www.deckcoatings.com
20420 S. Susana Road
Carson, CA 90810 U.S.A.
©2002 by Versatile Building Products, Inc. Rev 01/04