

Reliable.... *ICBO approved and Class A Fire Rated*

VERSA-DECK PLUS is an extremely tough, metal lath reinforced fiberglass deck coating system that is designed to be used over new and previously coated plywood and concrete walking deck surfaces. VERSA-DECK PLUS provides a durable, waterproof deck surface that is resistant to UV degradation and freeze-thaw cycling, while providing a Class-A one hour fire resistive assembly when combined with appropriate construction.

Simple.... *single component packaging prevents installation mistakes*

VERSA-DECK PLUS has been specially formulated for a well balanced combination of performance, ease of installation, and minimal down-time. Decking installations of VERSA-DECK PLUS perform well in a variety of climates and conditions, for many years. The simple, no mix formulation, virtually eliminates on-site mixing errors and assures the end user that the applied product is of the same high quality intended from the factory. Best of all, the system has been formulated to be the fastest installing system of its type on the market, with typical installations being completed in 1-2 days; fast installation keeps labor costs down, customers happy, and construction schedules on track.




Wide Range of Colors



Versa-Deck Plus installed over a typical walkway

An Illustration of the Multi-Step Process



Innovative.... *incorporating all the features you need*

Features:

- ✓ **Speed:** Fastest Installing System of its Kind on the Market, *Metal Lath Cement dries in 2 hours*
- ✓ **Quality:** ICBO Approved Product
- ✓ **Single Components:** Reduces on-site mixing errors
- ✓ **Safety:** Class-A One Hour Fire Rating
- ✓ **Water-Based:** Clean all Tools and Equipment with Soap and Water
- ✓ **Waterproof:** Seamless, Crack Resistant Nature Prevents Water from entering underlying structure
- ✓ **Slip-Resistant:** Variable Texture for all Environments to help prevent Slips and Falls
- ✓ **Breathable:** Prevents Dry-Rot by allowing Moisture to Escape from the Substrate
- ✓ **UV Stable:** Coating and Colorant will not fade, peel, chalk, or deteriorate under exterior exposure
- ✓ **VOC Compliant:** Compliant with ALL governing bodies and Air Quality Management Districts
- ✓ **Easy Maintenance:** Clean surface with mild soap and water
- ✓ **Color Choices:** Available in 15 standard colors or Custom color matching upon request.
- ✓ **Wind Uplift:** Bonded system allows installation at higher elevations in windy environments
- ✓ **Lightweight:** Only weighs 1.60 Lb. per square foot
- ✓ **Dimensional Stability:** Non-shrink mortar prevents curling and warping of deck

ICBO ES REPORT #6036		Los Angeles General Approval RR#25365	
Test Description		Result	
Weatherometer (ASTM G-26)		No Effect	
2000 Accelerated Hours			
Accelerated Aging ASTM (D-576 Mod.)		No Effect	
6 cycles D & E			
Fire Resistance (UBC 15-2)		Passes Class A Criteria	
Fire Resistance (ASTM E-119)		1 Hour Fire Resistive Assembly	
2x8 Joist @ 16" O.C. w/ 1/2" Type X gypsum wallboard ceiling and 5/8" plywood substrate topped with Versa-Deck Plus		Meets Temperature Requirements of U.B.C. Standard No. 7-1	
Bond Strength (ASTM C-297)			
Concrete		97 psi	
Exterior Plywood		148 psi	
Galvanized Metal		361 psi	
Abrasion ASTM D-1242		8 mil loss	
1000 cycle, 1Kg, #80TP			
Percolation (AC-39)		Zero Percolation	
Water Absorption (ASTM D-570)		Pass	
Freeze Thaw Cycling (ASTM C-67)		No Effect	
50 cycles			
Concentrated Load (AC-39)		Load .033" Rebound .019"	
500lb Load			
Chemical Resistance (ASTM D-2299)			
Industrial Detergent		No Effect	
Ammonia		No Effect	
Hydrochloric Acid		No Effect	
Chlorine		Pass	
Anti-Freeze		No Effect	
Turpentine		No Effect	
Paint Thinner		No Effect	
Kerosene		No Effect	

Quick Facts	Versa-Deck Plus	Ordinary Fiberglass	Urethane Decking	Slip-Sheeted Decking	Ordinary Metal Lath Deck
Breathable	✓	✓			✓
Direct Bond	✓	✓	✓		
Stopable	✓	✓			✓
Easy to install	✓				✓
Easy to Repair	✓				✓
Speed of Installation	✓				
Texture Options	✓	✓			
Water Cleanup	✓	✓		✓	✓
Single Components	✓		✓		

Versatile.... *multiple colors & designer finishes available*

COLOR SELECTIONS

Actual product color will vary on account of the limitations in the printing process. See actual color selector chart or sample of material for true color.



Antique White



Ivory Cream



Pinewood



Cottonwood



Beige



Buckskin



Mocha



Desert Rose



Terra Cotta



True Brick



Whisper Grey



Slate Grey



Dark Grey



Cape Cod Blue



Tennis Court Green



Staple the Metal Lath directly to the plywood using a 1" crown staple.



Pour fast setting Metal Lath Cement directly onto metal lath and start troweling .



Begin rolling Laminating Resins into Fiberglass.



Apply the Textured Basecoat with a hopper gun, trowel or roller.



Apply the Finish Resins using a brush and roller.

Start Enjoying Your New Deck with Versa-Deck Plus



Versatile Deck Coatings, Inc.
1-800-535-3325 • 310-635-6500
Fax 310-632-6516
www.deckcoatings.com
E-mail: sales@deckcoatings.com
20420 S. Susana Rd.
Carson CA 90810 U.S.A.

Versa-Deck Plus

versatile



deck coatings inc
deckcoatings.com

Manufacturers of:

- Pedestrian deck coatings
- Concrete overlayments
- Epoxy flooring
- Concrete stains
- Concrete countertops
- Waterproof membranes
- Concrete repair products



Fastest single component system of its kind

Distributed By: