Material Safety Data Sheet

Section 1: Product Information

Manufacturer's Name / Address: Trade Names: Versatop, Versacrete,

Versa-Deck Lath Mortar, Versa-Deck Texture Mortar #60 3:1, #90 Blend, Course Blend, Lath Cement, All Versatile Cements

Versatile Deck Coatings Inc. Chemical Family: Cementitous Mortar

2460 Lemon Avenue

Signal Hill, CA 90806

Info. Phone: Intended Use: Floor Mortar and Concrete

562-989-2499 Repair Systems

Emergency Phone: Infotrac 800-535-5053

Initial Issue Date: 3/19/2 Revision Date: NA Prepared By: M.M. Duarte

Prepared by: M. Duarte

Section 2: Hazardous Ingredients

Hazardous Component	OSHA PEL	ACGIH TLV	Other Limits	% (Optional)
Portland Cements (65977-15-1)	ND	ND	ND	9-50
Silicon Dioxide	10mg/m^3	10mg/M^3	ND	0-75
Calcium Carbonate (1317-65-3)	ND	ND	ND	0-85

VOC of Component: 0g/L VOC As Applied:0g/L

Section 3: Physical Data

Boiling Point (°C):NASpecific Gravity:2.9Vapor Pressure:NAMelting Point:NEVapor Density:NAEvaporation Rate:NA

(Air = 1) (Butyl Acetate = 1)

Solubility in Water: Slight pH: Alkaline when wet

Freezing Point NA

Coefficient of Oil/Water Distribution: ND

Appearance and Odor: Gray or white powder w/ no odor.

Odor Threshold: NE

Section 4: Fire and Explosion Hazard

Flash Point (°C): NA
Conditions of Flammability: NA

Flammable Limits: LEL: NA UEL: NA

Autoignition Temperature (°C): NA

Hazardous Combustion Products: None known.

Sensitivity to Impact: None
Sensitivity to Static Discharge: None
Extinguishing Media: NA
Special Firefighting Procedures: NA

Unusual Fire and Explosion None

Page 2 of 5	Material Safety Data Sheet	Product:	versacrete,	Versatop,	#60 Blends,	/#90 Blends,	Course	Mortar
Lath Cement								

Hazards:

Product: versacrete, Versatop, #60 Blends, /#90 Blends, Course Mortar,

Section 5: Health Hazard Data

Overexposure Effects: Respiratory, skin, and eye irritation.

Conditions Aggravated by Exposure: Asthma, pre-existing skin disorders.

Health Hazards (Acute and Chronic Exposures):

Eyes

Acute:

Drying, irritation, and redness.

Chronic:

ND

Skin Contact

Acute:

Drying, irritation, redness. Prolonged and repeated exposure to wet material may cause painful rash.

Chronic

Allergic dermatitis may develop in hypersensitive individuals.

Skin Absorption

Acute:

Not absorbed through skin.

Chronic:

NA

Inhalation

Acute:

Irritation, labored breathing, drying of the nose and throat.

Chronic:

Excessive inhalation may result in respiratory disease, including silicosis, pneumoconiosis, and pulmonary fibrosis. Symptoms are progressive with continued exposure and increasing age.

Ingestion

Acute:

Alkali burns of the mouth, throat, and gastrointestinal tract.

Chronic:

ND

Emergency and First Aid Procedures:

General:

If unconscious, provide artificial respiration. Seek medical assistance as necessary. Treat symptomatically.

Eves:

Flush with clean water for at least 15 minutes while holding the eyelids open. Obtain medical attention.

Skin:

Remove contaminated clothing immediately. Wash effected areas with soap and water for at least 15 minutes. Seek medical attention if symptoms persist.

Inhalation:

Move effected person from risk of further exposure. Administer oxygen or artificial respiration as necessary. Obtain medical attention.

Ingestion:

Do not induce vomiting. Give 250ml of milk or water to drink. DO NOT GIVE LIQUIDS TO AN UNCONCIOUS PERSON. Consult physician.

Carcinogenic Data:

NTP: ND

OSHA: Suspected IARC: YES

Toxicological Data:

ND

Section 6: Reactivity Data				
Chemical Stability: ⊠ Stable Conditions to Avoid: High humidity.	Unstable			
Incompatibility (Materials to Avoid)	: Fluorine, acids, water.			
Hazardous Decomposition Products:	Calcium Oxide.			
Hazardous Polymerization (Reactivity	ty): May Occur Will Not Occur			

Section 7: Spill and Leak Procedures:

Steps to be Taken in Case of Material Release or Spillage: Evacuate non-essential personnel. Equip cleaning crew with protective clothing inclusive of rubber boots and gloves, long sleeve shirts and pants. Contain spill. Cover with absorbent material. Collect material in open containers.

Waste Disposal Methods: Dispose at a licensed, permitted, waste disposal facility in accordance with federal, state, and local regulations.

Ecological Information: ND

Ecotoxicity: ND

Section 8: Special Protection Information

Engineering Controls: Local exhaust and general ventilation is recommended **Respiratory Protection**: NIOSH approved respirator must be worn. **Protective Gloves**: Gloves of butyl, nitrile, or neoprene rubber must be worn.

Eye Protection: Chemical goggles or full-face shield must be worn.

Other protective Equipment: Long sleeve shirts and pants must be worn. Eye wash station or shower should be locally accessible.

Section 9: Handling and Storage

General: Store away from moisture.

Section 10: Supplemental Information

Health: 2 Flammability: 0 Reactivity: 0

DOT Proper Shipping Name: Not regulated

Hazard Class : NA UN Number: NA Packing Group: NA **IMO Shipping Data**: ND ICAO/IATA Shipping Data: ND

TSCA (Toxic Substance Control Act):

All substances contained in this product are listed in the TSCA inventory. CERCLA (Comprehensive Response Compensation and Liability Act):

None.

SARA Title III:

ND

California Proposition 65: Below is a list of compounds known to the State of California to cause cancer, birth defects, or other reproductive harm:

Silicon Dioxide

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the accuracy of the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects, which may be caused by exposure to our products. Customers and users of this product must comply with all applicable health and safety laws, regulations and orders.