



SPEC DATA SHEET

Versa-Crete 2010

PRODUCT DESCRIPTION

Versatile Building Products VERSA-CRETE 2010 is a polymer latex admixture designed to be used with 2010 Stamping Mortar to create 1/4-1/2-inch stamped overlayment finishes.

COMPOSITION

Special proprietary blend of wetting agents, fillers, high strength cement, surfactants and latex polymers.

ADVANTAGES

- Rapid 30 minute set time
- Easy 2 component mix
- Accepts integral color & stains

LIMITATIONS

- Do not force dry
- Coverage rates may vary.
- Always wear protective clothing and equipment as required by OSHA and as necessary.
- Read Material Safety Data Sheets before commencing work.
- Material is not intended for use in submerged water or constant moisture conditions.

AREAS OF USE

- Restaurant Floors
- Showroom Floors
- Residential Floors
- Any Concrete Surface

COLORS

Multiple

PACKAGING and COVERAGE

Primer

2010 Liquid 5 Gal Pail

Thickness

2-3 Mills 1250-1500 sq. ft

Mortar

2010 Liquid

Thickness

1/4 -inch 125 sq. ft
1/2 -inch 62.5 sq. ft

2010 Stamping Mortar 50 Lb Bag

Thickness

1/4 -inch 25 sq. ft
1/2 -inch 12.5 sq. ft

FINISHES

Stamped

AVAILABILITY AND COST

Versatile Building Products are supplied through building material dealers. Prices vary with quantity and packaging. Quotations are made on request.

INSTALLATION

Refer to manufacturers detailed System Installation Guide.

COVERAGE

Refer to manufacturers detailed System Installation Guide.

MAINTENANCE

Maintain the protective topcoat or subsequent layer to prevent damage of the Versa-Crete. If the Versa-Crete is damaged, it can be repaired by sanding the surface, cleaning and then recoating the area with same materials.

TECHNICAL SERVICES

Technical services can be obtained by contacting:
VBP direct at 310-632-6500 or 800-535-3325.

Warranty

Versatile Building Products Inc guarantees that this product is free from manufacturing defects and complies with our published specifications. In the event that the buyer proves that the goods received do not conform to these specifications or were defectively manufactured, the buyer's remedies shall be limited to either the return of the goods and repayment of the purchase price or replacement of the defective material at the option of the seller. Versatile Building Products Inc (herein referred to as "seller") makes no warranty, expressed or implied, regarding the use of its products. Since use of this product is beyond the seller's control, the buyer assumes all risk of use. Seller's obligation shall be to replace material if found defective. Seller shall not be liable for any damage, injury, loss, direct or consequential, resulting from the use of its products. End user must determine if substrate is suitable for coating application before installing.